



EV CHARGING SOLUTION

DC Charger / DC City Charger

Features

- 50kW/100kW simultaneous charging
- Dynamic load distribution optimizes charging service
- RFID, credit card and ISO 15118 user identification
- OCPP and network connectivity enables system integration
- Modular design ensures high availability
- IP55 and small footprint provides high adaptability
- 94% power efficiency for energy-saving



Highway
Service



Parking



Service
Station



Commercial
Building



Fleet



Speed up Urban Life with EV Fast Charging


DC City Charger is an ideal solution for high efficiency urban charging service. It supports simultaneous charging output and load distribution to optimize utilization rate of the charging site. DC City Charger is compatible to OCPP which allows further backend system integration like user management, remote control and energy management.



Feature Highlights



Application Scenario



Specifications

Part Number	EVHE104-	
Power Input	Single Output	Dual Outputs
Input Rating	380-415Vac, 3-Phase, 50 / 60 Hz, L1, L2, L3, N, PE	
Power Factor	0.99 at nominal output	
Efficiency	94% at nominal output power	
Power Output		
Output Voltage	50 – 1000 Vdc	
Output Interface	DC output options: CCS2, CHAdeMO AC output option: Type 2 Socket	
DC Output Current	200A max.	
DC Output Power	100kW max.	
AC Output Current	3-Phase 32A max.	
AC Output Power	22kW max.	
Protection		
Protection	Over current, Under voltage, Over voltage, Surge protection, Short circuit, Over temperature, Ground fault	
User Interface & Control		
Display	7 inch LCD Touch Panel	
Support Language	English (Other languages available upon request)	
Push Buttons	1 Emergency Stop Button	
Charge Options	-	Simultaneous charging and configurable dynamic load distribution
User Authentication	ISO / IEC 14443 A / B Mifare RFID reader	
Communication		
Network Interface	Ethernet, Cellular, WLAN, Bluetooth	
Protocol	OCPP1.5-S, OCPP1.6-J, upgradable to OCPP2.0	
Environmental		
Operating Temperature	Operating from -30 °C to +50 °C, Derating from +50 °C to +60 °C	
Storage Temperature	-40 °C to +80 °C	
Humidity	< 95% relative humidity, non-condensing	
Altitude	4,000 m	
Mechanical		
Ingress Protection	IP55	
Enclosure Protection	IK10 according to IEC 62262	
Cooling	Forced air	
Charging Cable Length	4 m (Standard) ; 7.5 m (Optional)	
Dimension (D x H x W) / Weight *	590 x 1500 x 800 mm / 350 kg	
Regulation		
Certificate	CE	
Installation		
Accessory	Basement	

* Dimension and weight including 4 m charging connectors, subject to variants.
Product outlook depends on configuration. Specifications are subject to change without notice.



Delta Electronics (Netherlands) BV

Zandsteen 15, 2132 MZ Hoofddorp,
The Netherlands
TEL : +31 20 655-0900

Delta Electronics Inc.

3 Tungyuan Road, Chungli Industrial Zone,
Taoyuan City 32063, Taiwan
TEL : +886 3 4526107 E-mail : evcs@deltaww.com